


Firmware-Update testo Saveris™ Cockpit Unit

Pages
1/1


Please notice the following information before performing the Firmware Update of testo Saveris Cockpit Unit


- Before you do a Firmware-Update confirm all opened alarms at the Cockpit Unit.
- Stop all running tours at the Cockpit Unit.
- Disconnect the Cockpit Unit from the power supply. Shut it down or wait until it is powering down automatically.

Instruction Firmware-Update testo Saveris™ Cockpit Unit

1. Download the file [Firmware-Update Cockpit Unit](#) from the Testo website.
www.testo.org / Search for „Cockpit Unit“ / Tab „Downloads“ / Download „Firmware-Update Saveris Cockpit Unit“.
2. Connect the USB-cable with Saveris Cockpit Unit.
3. Press and hold the  UP-button of the Cockpit Unit.



4. Connect the Cockpit Unit via USB cable to a PC/Notebook
 - The LED of the Cockpit Unit shows a continuous red light
 - Cockpit Unit is displayed as a removable medium (*FWUPDATE*) in the Windows-Explorer
5. Release the  UP-button of the Cockpit Unit
6. Open Windows-Explorer and click on *FWUPDATE*



7. Delete the existing file in the directory *FWUPDATE*
8. Choose the target directory, where you have saved the new Cockpit Unit Firmware file and open this file folder.
9. Copy the new Firmware-file (05011024.bin) in the directory *FWUPDATE*
 - The Firmware Update of the Cockpit Unit is finished.