

	testo 865	testo 868	testo 871	testo 872	testo 875-2i	testo 882	testo 885	testo 890
Modelo	0560 8650	0560 8681	0560 8712	0560 8721	0560 0875 V2	0560 0882	0563 0885 V2	0563 0890 V2
Imagen								
Resolución de infrarrojos	160 x 120 Píxel	160 x 120 Píxel	240 x 180 Píxel	320 x 240 Píxel	160 x 120 Píxel	320 x 240 Píxel	320 x 240 Píxel	640 x 480 Píxel
Resolución SuperResolution	320 x 240 Píxel	320 x 240 Píxel	480 x 360 Píxel	640 x 480 Píxel	320 x 240 Píxel	640 x 480 Píxel	640 x 480 Píxel	1280 x 960 Píxel
NETD (sensibilidad térmica)	120 mK	100 mK	90 mK	60 mK	< 50 mK bei +30 °C	< 50 mK bei +30 °C	< 30 mK bei +30 °C	< 40 mK bei +30 °C
Campo de visión (FOV)	31° x 23°	31° x 23°	35° x 26°	42° x 30°	32° x 23°	32° x 23°	30° x 23°	42° x 32°
Campo de visión Objetivo gran angular (FOV)	31° x 23°	31° x 23°	35° x 26°	42° x 30°	32° x 23°	32° x 23°	30° x 23°	42° x 32°
Campo de visión Teleobjetivo (FOV)	-	-	-	-	9° x 7° (opcional)	-	11° x 9° (opcional)	15° x 11° (opcional)
Campo de visión Súper teleobjetivo (FOV)	-	-	-	-	-	-	5° x 3,7° (opcional)	6,6° x 5° (opcional)
Resolución geométrica (IFOV)	3,4 mrad	3,4 mrad	2,6 mrad	2,3 mrad	3,3 mrad (Tele: 1,0 mrad)	1,7 mrad	1.7 mrad (Tele: 0,6 mrad)	1.13 mrad (Tele: 0.42 mrad)
Enfoque	Foco fijo	Foco fijo	Foco fijo	Foco fijo	Enfoque manual	Enfoque manual y motor de enfoque	Enfoque automático y manual	Enfoque automático y manual
Distancia mínima de enfoque Infrarrojos	< 0,5 m	< 0,5 m	< 0,5 m	< 0,5 m	0.1 m (Tele: 0.5 m)	0,2 m	0,1 m (Tele: 0.5 m)	0,1 m (Tele: 0.5 m)
Rango de medición	-20 ... +280 °C	-30 ... +100 °C 0 ... +650° C	-30 ... +100 °C 0 ... +650° C	-30 ... +100 °C 0 ... +650° C	-30 ... +100 °C 0 ... +350 °C +350 ... +550 °C (Alta temp)	-20 ... +100 °C 0 ... +350 °C +350 ... +550 °C (Alta temp)	-30 ... +100 °C 0 ... +350 °C 0 ... +650 °C +350 ... +1200°C (Alta temp)	-30 ... +100 °C 0 ... +350 °C 0 ... +650 °C +350 ... +1200°C (Alta temp)